

WALL MOUNT LOUDSPEAKER

LA-IWM



The LA-IWM model can be used in locations such as atriums where a suspended loudspeaker might be difficult to install or awkward in appearance. A side view (left) shows the swivel bracket that allows the loudspeaker to be positioned in the desired direction.



The loudspeaker shown from the front.

SPECIFICATIONS

Audio Performance

Masking Output	81 dBA maximum
Paging Output	81 dBA maximum

Driver Specifications

Frequency Range	100 to 10,000 Hz
Dimension	7.6 cm; 3 inches
Power Handling	10 W (RMS)
Sensitivity	84.2 dBA @ 1W / 1m
Magnet Structure	58 g; 2.05 oz
Impedance	16 ohms

Connections

Loudspeaker Input	2-pin
-------------------	-------

Cabling

Loudspeaker to Hub	Integrated cable assembly
--------------------	---------------------------

Physical Specifications

Dimensions (W x H x L)	12 x 11 x 24.5 cm; 4.7 x 4.3 x 9.7 inches
Enclosure	Metal and plastic
Color	White
Weight	0.91 kg; 2 lb

Mounting

Swivel bracket for wall mounting

Warranty

5 years; see *LogiSon® Product Warranty* for details

Certifications

Meets UL, FCC and CE standards; RoHS compliant