

Fail-Safe Power Solution

Use this robust power solution featuring overcurrent and overvoltage protection, power load sharing, automatic fault detection, and power redundancy to ensure uninterrupted operation.



The Fail-Safe Power Solution is housed inside a metal enclosure.

SPECIFICATIONS



FPS 120 (120W)

Input	100-120/200-240 VAC, 50/60 Hz, 3/2 A
Output	24 VDC, 4 A maximum
Dimensions (L x W x H)	40.6 x 40.6 x 15.2 cm; 16 x 16 x 6 inches
Weight	10.16 kg; 22.4 lbs
Operating Temperature	0 to +35°C; 32 to 95°F
DC Output Status Display	LED green
Mounting Position	Vertical
Warranty	5 years; see LogiSon® Product Warranty for details

FPS 250 (250W)

Input	100-120/200-240 VAC, 50/60 Hz, 3.6/2 A
Output	24 VDC, 10 A maximum
Dimensions (L x W x H)	40.6 x 40.6 x 15.2 cm; 16 x 16 x 6 inches
Weight	12.2 kg; 26.8 lbs
Operating Temperature	0 to +35°C; 32 to 95°F
DC Output Status Display	LED green
Mounting Position	Vertical
Warranty	5 years; see LogiSon® Product Warranty for details

FPS 500 (500W)

Input	100-120/200-240 VAC, 50/60 Hz, 9/6 A
Output	24 VDC, 20 A maximum
Dimensions (L x W x H)	45.7 x 45.7 x 15.2 cm; 18 x 18 x 6 inches
Weight	16.3 kg; 36 lbs
Operating Temperature	0 to +35°C; 32 to 95°F
DC Output Status Display	LED green
Mounting Position	Vertical
Warranty	5 years; see LogiSon® Product Warranty for details

Complies with UL 60065, 7th Edition, 2007-12-11 (Audio, video and similar electronic apparatus – Safety requirements), CAN/CSA – C22.2 No. 60065-03, 1st Edition, 2006-04 and A1:2006 (Audio, video and similar electronic apparatus – Safety requirements). Each component is UL and EMI tested and certified and approved for use with the LogiSon Acoustic Network.