

Programmable Keypad + Remote

Offer occupants on-demand control of the sound masking and paging settings in private offices and meeting rooms, or anywhere else there's a need for individual control. Prior to use, define what area each keypad controls, the functions it offers and the degree to which occupants can change settings.

User Instructions

To activate the keypad, press any key. If the desired function isn't highlighted, press the Select key to choose either Masking or Paging. The screen displays the current setting for that function. To increase or decrease the volume, press the + or – key. To mute the function, press the Mute key. The screen displays two dashes. To un-mute, press the Mute key again. To change the paging channel, press the Select key until the screen displays a C and then press the + or – key.

SPECIFICATIONS



PK + PKR

Control Performance	Masking and paging volume control, masking and paging mute, paging channel selection, remote control receiver enable/disable
Masking Performance	
Volume Adjustment Range	99 step range in 0.5 dBA steps + mute
Volume Restriction	Administrator defines minimum and maximum
Function Restriction	Administrator enables or disables functions
Paging Performance	
Volume Adjustment Range	99 step range in 0.5 dBA steps + mute
Volume Restriction	Administrator defines minimum and maximum
Function Restriction	Administrator enables or disables functions
Paging Channel Selection	Zone 1, 2, 3 or none
Connections	
Network In/Out	6-pin
Power	
Input	30 VDC
Consumption	Maximum 6 W
Zoning	
Method	Electronically zoned using Network Control Panel or Acoustic Network Manager Software
Zone Size	No limit
Physical Specifications	
Dimensions (W x H x D)	4 x 10.4 x 4.6 cm; 1.58 x 4.1 x 1.825 inches
Color	White
Weight	120 g; 4.2 oz
Display	2-digit LED
Keypad	4-key membrane panel
Remote Control	
Remote Receiver	Infrared remote control receiver for use with PKR-1
Function Restriction	Administrator enables or disables function
Mounting	Single-gang wall box with white, Decora-style faceplate
Security	
Function Restrictions	See restrictions noted above
Warranty	5 years: see LogiSon® Product Warranty for details
Certifications	Meets UL, CE, ACMA (C-Tick) and FCC standards; RoHS compliant